

SERIES 2286.0150 EPIC UNIVERSAL PRIMER FOR DECORATIONS
Use

The quartz based universal primer is suitable for indoor use on new walls or old paints still well anchored and not chalking.

Its granulometry allows the easy application of our decoration effects, thus obtaining an even finish homogeneous.

Main features

White water-based wall paint.

Its main features are:

- high coverage;
- waterproof;
- easy to apply.

Technical features (data surveyed at 20°C)

Brookfield viscosity	sec.	2500 ± 300
Specific gravity	kg/l	1,550 ± 0,050
Solids content	%	67 ± 2
Theoretical spreading rate	sqm/l	7 - 8
Film gloss	gloss	matt
Thinner	code	water
Dry to dust	minutes	5 - 10
Dry to touch	minutes	20 - 30
Dry in depth	hours	2 - 4
Dry to recoat	hours	4 - 6

Methods of application

Brush	Thin with	water at 20 - 25%
Roller	Thin with	water at 15 - 20%
Mix the product well by slowly adding water until obtaining the desired viscosity. Do not apply if the temperature is lower than 5°C. Wash brushes and tools with water immediately after use. Keep the product away from frost.		

Recommended painting cycles
ON NEW WALLS

Surfaces must be seasoned, dry, free of dust and all impurities, included non adherent sand. A coat of water-based fixative or solvent-based isolating fixative increases the adhesion and eliminates the chalking.

ON PAINTED WALLS

Remove peeling paints by scraping and brushing. Tempera paintings must be removed too.

Notes

The hardened stains of the product can be easily removed with Thinner Nitro 9210.0012

27/03/2015