

**SERIES 2288.1300 EP!C FUNK SILVER – DECORATIVE COATING ANTIQUE
PATINA EFFECT
2288.1500 EP!C FUNK GOLD**

Use

For building interior use. Thanks to the pearlescent pigments contained in this product, it is possible to obtain surfaces with an antique patina look and metallic reflections. It allows to give value to all the surfaces where it's applied, even when the substrate is not perfectly smooth. The final result is characterized by a light and shade effect which can vary depending on the used tools and on the substrate where the product is applied.

Available in the colours:

2288.1300 Silver

2288.1500 Gold, these are bases that can be tinted with our colorimetric systems Colormaker and Colormaker Aqua in the colours shown on the Funk colour card.

Main Features:

Water based paint for interiors with low V.O.C. content, provided with:

- Excellent resistance to impacts and chalking;
- Washability
- Easy to apply, the application is made with one coat only

Technical features (data surveyed at 20°C)

Brookfield viscosity	cps.	
Specific gravity	kg/l	
Theoretical spreading rate	mq/l	
Film appearance	gloss	Matt
Thinner	code	Water
Dry to touch	minutes	
Dry in depth	hours	
Chalking level (UNI EN ISO 4628:2003)		1 (0= no chalking; 5 = high chalking)
Vapour permeability (UNI EN ISO 10560:1996)		Sd=0.303 m (thickness= 60µm) µ= 505 High vapour permeability (Class V 1)
Resistance to the washing and abrasion	cycle	
Dirt pick-up	ΔL	3,5 (low)

Application Modalities

By brush, and flexible plastic trowel		If necessary dilute with maximum 5% of water
<p>Apply Funk in one coat using crossed movements and spreading the pearlescent pigments non-uniformly on the surface, leaving some smooth and some relief areas. As soon as the film of the paint begins to dry up, work softly the surface with a flexible plastic trowel, at an angle of approx. 30° to the surface, until obtaining the desired effect.</p> <p>With this product it's possible to obtain many different effects depending on the imagination and creativity of the applicator. Do not apply the product with as temperature below 5° C.</p>		

Recommended painting cycles

NEW WALLS – Before starting make sure that the surface is perfectly smooth, in case it's necessary to smooth it it's suggested to use EP!C RASANTE PER DECORATIVI code 2310.0100. Insulate with Titancril Code 2340.0003; apply one or two coats of universal primer for Decorations series 2286.0150, or a quarts paint like Acrylquartz series 2270.0000 in the desired shade.

ALREADY PAINTED WALLS – Make sure that the old paint is well anchored to the substrate and that it's a good quality paint. If not, remove the non-adherent or the old chalking paint and proceed preparing the surface as per the "New walls" section.

Queste note sono frutto della nostra migliore esperienza. Tuttavia essendo molti gli impieghi e le tecniche di applicazione non possiamo assumere garanzie per ogni singolo caso.

These applicative notes are given to the best of our experience. However being many uses and application technics we can not guarantee for each single case.

Notes

Brushes and tools must be washed immediately after the use. Keep the product away from frost.

Stability

The finished product is conserved in a well sealed can, at temperature higher than 5°C and lower than 30°C, does not present any stability problem. The maximum storage period suggested is 12 months.

27/03/2015

Queste note sono frutto della nostra migliore esperienza. Tuttavia essendo molti gli impieghi e le tecniche di applicazione non possiamo assumere garanzie per ogni singolo caso.

These applicative notes are given to the best of our experience. However being many uses and application technics we can not guarantee for each single case.