

**SERIES 2288.2300 EPIC TANGO SILVER – DECORATIVE PEARLESCENT COATING WITH VELVET EFFECT**  
**2288.2500 EPIC TANGO GOLD**  
**2288.2600 EPIC TANGO RED**

### Use

EPIC TANGO is the water-based decorative finish for interiors, softly metalized, with an elegant decorative effect with velvet tactile sensations. It's formulated with high quality pigments, which are oriented during the application creating a soft chromatic solution on the surface.

EPIC TANGO is available in the following colors:

2288.2300 - EPIC TANGO SILVER

2288.2500 - EPIC TANGO GOLD

2288.2600 - EPIC TANGO RED, they can be tinted with our colorimetric systems Colormaker and Colormaker Aqua

in the colors shown on EPIC TANGO color card.

### Main Features:

Water based paint for interiors with low V.O.C. content with the following features:

- Easy to apply, the application is made with one coat only
- Excellent resistance to impacts and chalking;
- Washability

### Technical features (data surveyed at 20°C)

|  |         |       |
|--|---------|-------|
| Brookfield viscosity                   | cps.    |       |
| Specific gravity                       | kg/l    |       |
| Theoretical spreading rate             | mq/l    |       |
| Film appearance                        | gloss   | Matt  |
| Thinner                                | code    | Water |
| Dry to touch                           | minutes |       |
| Dry in depth                           | hours   |       |
| Resistance to the washing and abrasion | cycle   |       |

### Application Modalities

|  |  |  |
|--|--|--|
| By brush, and plastic trowel   |  | Ready to use, if necessary dilute with maximum 1-2% of water |
| <p>Apply the first coat of TANGO by brush with crossed movements, spreading the product uniformly on the surface. When the surface is totally dry, apply the second coat on small portions of 1-2 square meters of surface, always with crossed movements, orienting the pigments and creating the finishing texture. After few minutes, with the product which is not dry yet, work the surface with a plastic trowel in different directions, until obtaining the desired texture. With this product it's possible to obtain many different effects depending on the imagination and creativity of the applicator. Apply the product with as temperatures within +5° C and +35°C and relative humidity not above 75%..</p> |  |  |

### Recommended painting cycles

**NEW WALLS** – Before starting make sure that the surface is perfectly smooth, in case it's necessary to smooth it it's suggested to use EPIC RASANTE PER DECORATIVI code 2310.0100. Insulate with Titancril Code 2340.0003; apply one or two coats of universal primer for Decorations series 2286.0150, or a quarts paint like Acrylquarz series 2270.0000 in the desired shade.

**ALREADY PAINTED WALLS** – Make sure that the old paint is well anchored to the substrate and that it's a good quality paint. If not, remove the non-adherent or the old chalking paint and proceed preparing the surface as per the "New walls" section.

### Notes

Brushes and tools must be washed immediately after the use. Keep the product away from frost.

### Stability

The finished product is conserved in a well sealed can, at temperature higher than 5°C and lower than 30°C, does not present any stability problem. The maximum storage period suggested is 12 months.

Queste note sono frutto della nostra migliore esperienza. Tuttavia essendo molti gli impieghi e le tecniche di applicazione non possiamo assumere garanzie per ogni singolo caso. These applicative notes are given to the best of our experience. However being many uses and application technics we can not guarantee for each single case.

27/03/2015