

# CORROD

## Product description

Corrod is a rust effect paint with activator that was developed by Impera Italia to enable you to transform almost any surface into a feature with a weathered, corten steel look. This rusted iron-like patina can be further customised by applying the activator on more layers or in a greater amount to create a more rusted look.

## Application Instructions

Corrod is ready to use and can be applied on a wide variety of surfaces such as wood or MDF boards, walls, ceilings and even metal or glass. First apply Corrod base by brush, sponge or even trowel and leave to completely dry. Next apply Corrod activator R either by brush or sponge in order to produce a yellow or red rust look. When dry, apply either the full or a partial amount of Corrod activator C to create an oxidised look. Corrod stabiliser should then be applied with 12 to 24 hours after the activator in order to ensure that the look does not change further.

## Surface Preparation

Make sure the surface is completely dry, dust free and all impurities have been removed. In case of mould, treat the surface with suitable specific products. Brush or remove any efflorescence and old peeling paint or wallpaper. Once the surface has been prepared you must apply Corrod primer, diluted with 1:3 of water prior to application of the paint. Wait for 2 to 4 hours for the primer to get completely dry. Corrod paint comes in a tin with high thixotropy and viscosity therefore it is necessary to agitate it vigorously before application either by hand or with steel mixer. When applying the activator, do so in stages, to better control the appearance. The more activator that is applied the more the colour will change.

## Cleaning of tools

Tools should be cleaned immediately after use with water.

## Technical Specifications

1 Kg of Corrod covers approx. 5sqm depends of thickness of application and absorption of the surface.

## Recommendations:

Do not apply Corrod if the substrate, air or product temperature is lower than +5°C and higher than +35°C, nor under direct sun light.

## Storage

Storage temperature: 5 - 30 ° C. Corrod paint should be used preferably within 2 years from date of purchase and should be stored in the original container, under the appropriate temperature conditions.