

SIOLOC

Product description

Sioloc is a smooth Metallic Feature Wall Paint which will enable you to create a high-end look. It is extremely easy to apply, you can create several stunning effects with contemporary or traditional design quickly.

Application Instructions

Sioloc is ready to use and can be applied on new and old plasters concrete surfaces, gypsum plasters plasterboard M OF, timber and metal surfaces after Sioloc primer

It can be applied by sponge or brush and the effect can be created by brush, sponge, or a Venetian plastering trowel Sioloc should not be diluted, but in case of extreme heat or suction it can be diluted by water up to 5%.

Surface Preparation

Make sure the surface is completely dry, dust free and all impurities have been removed. In case of mould, treat the surface with suitable specific products. Brush or remove any efflorescence and old peeling paint or wallpaper. If you are planning to apply Sioloc on a dusty, chalky or high porous area, you should use Atomo (To be applied before Sioloc) This will help to consolidate the surface. Once the surface has been prepared you must apply the primer, diluted with 1:3 of water prior to application of the paint. Wait for 2 to 4 hours for the primer to get completely dry.

Before applying Sioloc, stir the pot and apply it with a roller or flexible plastic trowel. Once you've applied a half square metre and the paint has started to settle (approx 2 mins), open and stir the paint, then apply the 1st coat of Sioloc using a flexible plastic trowel.

Cover about 1-2 square metres (11 to 22 square feet) at a time and then flatten the area by spatula for the best look! Alternatively, you can leave it as it is. Make sure to leave the first coat to dry for 4-6 hours before you put on the second one!

Apply the 2nd coat the same way as the previous coat.

SIOLOC

Cleaning of tools

Tools should be cleaned immediately after use with water.

Technical Specifications

1 Kg of Sioloc covers approx 5 sqm depends on thickness of application

Recommendations

Do not apply Sioloc if the substrate, air, or product temperature is lower than +5°C and higher than +35°C, nor under direct sun light.

Storage

Storage temperature 5- 30 °C Sioloc paint should be used preferably within 2 years from date of purchase and should be stored in the original container, under the appropriate temperature condition.

