

SIOLOC SUEDE

Product Description

Sioloc Suede is a semi-matt silky wall paint that can be used for any indoor project. Once you apply it, you can create a soft, suede-look with overlapping layers. It is extremely easy to apply, you can create several stunning effects with contemporary or traditional design quickly.

Application Instructions

Sioloc Suede can be applied using a Flexible Plastic Trowel, or a Medium Pile Roller. Sioloc Suede should not be diluted with water, but in case of extreme heat or suction, it can be diluted by water up to 5%.

Surface Preparation

Make sure the surface is completely dry, dust free and all impurities have been removed. In case of mould, treat the surface with suitable specific products.

Brush or remove any efflorescence, and old peeling paint or wallpaper. If you are planning to apply Sioloc Suede on a dusty, chalky, or high porous area, you should use Atomo (**to be applied before Sioloc Suede primer**). This will help to consolidate the surface.

To increase water repellency and wipeability we recommend applying 2 coats of Impera Matt.

Once the surface has been prepared, you must dilute the primer with 30% water (For 1L of primer dilute with 300mL of water, and for 0.5L of primer dilute it with 150mL of water). Wait for 2 – 4 hours for Sioloc Suede primer to be completely dry.

Before applying Sioloc Suede, stir the pot thoroughly, apply the first coat using a Flexible Plastic Trowel. Once you've applied between 1-2 sqm, flatten it with a spatula, or a plastic trowel for the best look, or just leave it as it is. Leave the first coat to dry for 4-6 hours.

Apply the second coat the same way as the previous one.

Cleaning of Tools

Tools should be cleaned immediately after use with water.

SIOLOC SUEDE

Technical Specifications

1 KG of Sioloc Suede covers approximately 5 sqm depending on the thickness of the application.

Recommendations

Do not apply Sioloc Suede if the substrate, air, or product temperature is lower than +5°C and higher than +35°C, nor under direct sunlight.

Storage

Storage temperature 5- 30 °C Sioloc Suede paint should be used preferably within 2 years from date of purchase and should be stored in the original container. under the appropriate temperature conditions.