

SIOLOC SUEDE

Product description

Sioloc Suede is a smooth Metallic Feature Wall Paint which will enable you to create a high-end look. It is extremely easy to apply, you can create several stunning effects with contemporary or traditional design quickly.

Application Instructions

Sioloc Suede is ready to use and can be applied on new and old plasters, concrete surfaces, gypsum plasters, plasterboard, MDF, timber and metal surfaces after Sioloc Suede primer.

It can be applied by sponge or brush and the effect can be created by brush, sponge, or a Venetian plastering trowel. Sioloc Suede should not be diluted, but in case of extreme heat or suction it can be diluted by water up to 5%.

Surface Preparation

Make sure the surface is completely dry, dust free and all impurities have been removed.

In case of mould, treat the surface with suitable specific products. Brush or remove any efflorescence and old peeling paint or wallpaper. If you are planning to apply Gimcyn Luxury on a dusty, chalky or high porous area, you should use Atomo (To be applied before Sioloc Suede Primer). This will help to consolidate the surface. Once the surface has been prepared you must apply Sioloc Suede Primer, dilute it with 1:3 of water prior to the application of the paint. Wait 2 to 4 hours for the primer to get completely dry.

Before applying Sioloc Suede, stir the pot and apply it with an Italian special effect brush.

Once you've applied a half square metre and the paint has started to settle (approx 2 mins),

the effect can be changed or finalized with a tobacco sponge. In case you do a brush effect,

use the effect brush. The finish will be touch dry within an hour and completely dry after 12

hours. Only a single coat is needed for the effect, but in case it's needed more paint can be put on the surface by sponge.

SIOLOC SUEDE

Cleaning of tools

Tools should be cleaned immediately after use with water.

Technical Specifications

1 Kg of Sioloc Suede covers approx 5 sqm depends on thickness of application

Recommendations

Do not apply Sioloc Suede if the substrate, air, or product temperature is lower than +5°C and higher than +35°C, nor under direct sun light

Storage

Storage temperature 5- 30 °C Sioloc Suede paint should be used preferably within 2 years from date of purchase and should be stored in the original container, under the appropriate temperature conditions.

