

SIOLOC SUEDE

Product description

Sioloc Suede is a smooth Metallic Feature Silky paint which will enable you to create a high-end look. It is extremely easy to apply, you can create several stunning effects with contemporary or traditional design quickly.

Application Instructions

Sioloc Suede is ready to use and can be applied on new and old plasters, concrete surfaces, gypsum plasters, plasterboard, MDF, timber and metal surfaces after Sioloc Suede primer.

It can be applied by sponge or brush and the effect can be created by brush, sponge, or a Venetian plastering trowel. Sioloc Suede should not be diluted, but in case of extreme heat or suction it can be diluted by water up to 5%.

Surface Preparation

Make sure the surface is completely dry, dust free and all impurities have been removed. In case of mould, treat the surface with suitable specific products. Brush or remove any efflorescence and old peeling paint or wallpaper. Once the surface has been prepared you

must apply Sioloc Suede primer. Dilute Sioloc Suede primer with 30% of water (0.5L of primer with 150mL water, or, 1L of primer with 300 mL water), and apply it with a short pile, or mohair roller. Wait for 2 to 4 hours for the primer to get completely dry.

Before applying Sioloc Suede, stir the pot and apply it with an Italian special effect brush. Once you've applied a half square metre and the paint has started to settle (approx. 2 mins), the effect can be changed or finalised with a tobacco sponge. In case you do a 'brush effect', use the effect brush. The finish will be touch dry within an hour and completely dry after 12 hours. Only a single coat is needed for the effect, but in case it's needed more paint can be put on the surface by sponge.

Cleaning of tools

Tools should be cleaned immediately after use with water.

Technical Specifications

1 Kg of Sioloc Suede covers approx. 5sqm depends on thickness of application

Recommendations:

Do not apply Sioloc Suede if the substrate, air, or product temperature is lower than +5°C and higher than +35°C, nor under direct sun light.

Storage

Storage temperature: 5-30°C. Sioloc Suede paint should be used preferably within 2 years from date of purchase and should be stored in the original container, under the appropriate temperature conditions.

Impera Italia
33-35 the Market Place, Falloden Way,
NW11 6JY, London
Tel: +44 (0) 333 012 4396


IMPERA ITALIA™
luxury | design | worldwide