

SERIES 2286.0010 EPIC SAMBA - SILOPAINT GLAZING – SILOXANE PAINT FOR GLAZING EFFECT
Uses

In building in order to give to the painted support a particular glazing effect, in a simple and soft way. It can be applied both, on new and on already painted walls, and it is suitable for outdoor and indoor use. The product's composition ensures an excellent transpiring and water repellent effect, especially if used as final coat on Silopaint 2280.0050 G.F. or Silopaint 2281.0050 G.G. It can be coloured with the Colormaker and Colormaker Aqua systems in the colours included in Silopaint Velature colour card. All the colours produced with oxide colorants are resistant to the sunrays, then they are particularly suitable for exterior application.

General data

Semitransparent mural paint, based on siloxane resins. Its main characteristics are:

- high water repellence (DIN norm 52617) = W24:0,35
- excellent permeability to water vapour (UNI norm 9396) = SD:0,14
- non-saponifiable
- high washability
- high resistance to the effect of the weather
- easy to apply

Technical features (data gathered at the temperature of 20°C)

Brookfield viscosity	cps.	1150 ± 200
Specific gravity	kg/l	0,960 ± 0,030
Solids	%	14 ± 1
Theoretical spreading rate	mq/l	15-20 (mq/kg=4,5 - 5)
Appearance of the film	gloss	Satin
Thinner	code	Water
Dust free	Minutes	15-30
Touch free	Minutes	40 - 60
Dry in depth	minutes	2 - 4
Over painting	Hours	2 – 4

Application method

By brush - sponge	Diluite with	Water at 25 - 30%
By roller	Diluite with	Water at 20 - 30%

The dilution percentage is very variable according to the intensity of the shade, to the desired effect and to the absorption level of the support. The yield can vary according to the absorption of the wall, to the roughness of the surface and to the method of application.

Accurately mix the product, slowly adding water until getting the desired application viscosity.

Do not apply the product with a temperature lower than 5° C

Wash brushes and tools right after using them. Keep the product freeze-safe.

Recommended painting cycles
NEW SURFACES

Apply Samba on surfaces adequately prepared with one coat of Universal Primer for decorative effects series 2286.0150.

For exterior use: On surfaces prepared with acryl-siloxan/siloxan paints or coatings Series 2270-2281-2282.

The application of Samba must be done with the use of the appropriate tools, in order to obtain the desired effect: brush, sponge, gloves.

Apply the first coat in a uniform way, and when the product is still wet, remove any excess product from the surface. After minimum 4-6 hours apply the second coat in order to obtain the desired effect.

With this product it is possible to obtain various effects, according to the fantasy of the applicator.

27/03/2015

Queste note sono frutto della nostra migliore esperienza. Tuttavia essendo molti gli impieghi e le tecniche di applicazione non possiamo assumere garanzie per ogni singolo caso.
 These applicative notes are given to the best of our experience. However being many uses and application techniques we can not guarantee for each single case.