

CONCRETE PAINT

PRODUCT DESCRIPTION

Concrete Paint was designed with the intention of making the sought after concrete look, approachable to DIY users, whilst giving professionals a straightforward, reliable material whose genuine authenticity impresses even more so because of its simple application.

For a smooth concrete look, universal primer (smooth) should be applied beforehand.

For a rougher, natural concrete look, textured primer (gritty) is recommended instead.

PRODUCT INFORMATION

Coverage: 1.5kg per 5sqm on 2 coats.

Dilution: 6 parts powder: 5 parts water. For 1.5kg powder, add 1.25L of water.

Coats: 2.

Drying time: 2+ hours.

Workability: Due to the hydraulic binders in the material, once mixed with water, the product will begin to harden. The best workability is achieved in the first 120 mins. We recommend only mixing the amount that is to be used during this time.

Tools Required: Medium or long pile roller, mixing blade or small drill with paddle, spatula (150mm recommended).

Storage: At least 1 year when stored between +5C and +35C and kept out of direct sunlight.

INSTRUCTIONS FOR USE

- It is important to ensure that you apply the correct type of primer depending on the type of application you are trying to achieve. Textured primer is gritty and therefore ideal for creating textured surfaces, whilst universal primer is smooth. Either one of these should be done beforehand to give the surface the best possible adhesion for the application of Concrete Paint.
- Prepare the desired amount of powder, ensuring to maintain the correct mixing ratio. Once prepared, please leave the mixture to rest for 5-10 mins before beginning the application.
- Apply Concrete Paint by roller, using irregular movements to avoid repetitive patterns. The first coat can take 1 to 2 hours to dry. Once dry, before going onto the second coat, use the spatula to remove any lumps that may have formed on the first coat by scraping them off. Apply the second coat in the same way as the first. Leave until it begins to dry (not too much), then use the spatula to flatten the paint to the desired look. Professionals can choose to use a Venetian plastering trowel.

•



CONCRETE PAINT

- In order to get the best durability for your finish, please contact the office for guidance on choosing the right protector. Bear in mind that no protector should be applied until at least 24 hours after the final coat of Concrete Paint.

NOTES

The technical chart has been written by Impera Italia and the included information is based on our tests.

This technical information is intended as a rough guide. Due to the varying conditions it's essential to check the suitability of the product and test the effectiveness on a sample.

Impera Italia is not responsible for improper or incomplete surface preparation, assessment, mistakes of the design or application or any issue connected to human error when using the product.

