

Product Data Sheet

Description

A blue coloured self-supporting shower former with a pre-formed minimum fall of 2% that can be used with vinyl, tiles, resin and micro-cement floor coverings.

Advantages

Slimline - 22mm at the outer edges allowing barrier-free installation with most timber applications in the UK.

Self-Supporting - Can span joists.

Easy to install - It simply replaces the area where the floorboards have been removed.

Can be used in concrete floors.

Composition

Resin gel and reinforced fibre glass.

Made with 50% recycled material.

Trimming and Drilling

The material can be cut to size with a diamond saw.

The material is non brittle and can therefore be drilled using a masonry drill.

Waterproof

This has been tested for water absorption (ASTM C413) giving a result of 0.2%.

Density

1.25/cm³, estimated weights of the units are therefore -

900mm x 900mm = 17kg 1000mm x 1000mm = 23.8kg 1200mm x 800mm = 24kg

1135mm x 770mm = 23kg 1200mm x 900mm = 24kg 1200mm x 1200mm = 30kg

1300mm x 800mm = 24kg 1450mm x 1150mm = 32kg 1650mm x 900mm = 32kg

1400mm x 900mm = 27kg 1500mm x 800mm = 29.5kg 1800mm x 800mm = 32kg

Strength

Results from laboratory testing shows the tray, supported just at each corner, supported 1m apart can hold a central load test of at least 470kg. Tests have shown the Maxxus deck Has virtually no deflection, making it the best performing floor former for tile application. The tray is not deformed by point loading. It is therefore suitable for use with shower chairs.

Drainage

All Maxxus decks have an in-built gradient leading to the designed to fit Minimax drainage Gully for vinyl or tile.

