


AXXUS

Maxxus Linear Product Data Sheet




1200 x 900 x 22mm 600






1600 x 900 x 22mm







1400 x 900 x 22mm 450



Description

A blue coloured self-supporting shower former with a pre-formed minimum fall of 2% That can used with tiles.

Advantages

Slimline - 22 or 24mm at the outer edges allowing barrier-free installation with most timber applications in the UK.

Self-Supporting - Can span joists.

Easy to install - It simply replaces the area where the floorboards have been removed. Can be used in concrete floors.

Composition

Resin gel and reinforced fibre glass.

Made with 50% recycled material.

Trimming and Drilling

The material can be cut to size with a diamond saw.

The material is non brittle and can therefore be drilled using a masonry drill.

Waterproof

This has been tested for water absorption (ASTM C413) giving a result os 0.2%.

Density

1.25/cm3, estimated weights of the units are therefore -

1200mm x 900mm = 24kg 1200mm x 1200mm = 30kg 1600mm x 900mm = 32kg 1400mm x 900mm = 27kg 1500mm x 900mm = 30kg 1500mm x 1200mm = 40kg 1800mm x 900mm = 38kg

Strength

Results from laboratory testing shows the tray, supported just at each corner, supported 1m apart can hold a central load test of at least 470kg. Tests have shown the Maxxus deck Has virtually no deflection, making it the best performing floor former for tile application. The tray is not deformed by point loading. It is therefore suitable for use with shower chairs. Noggins should be installed to form a supporting cage around the linear drain hole for additional support of the Living Linear Drain gully system.

Drainage

All Maxxus decks have an in-built gradient leading to the designed to fit Living Linear drainage gully for vinyl or tile.

