

INFINITY

Product Description

Infinity is an extravagantly soft, velvety paint of the highest quality. The material is soft to the touch, and really comes to life in areas where it can reflect light and show the different shades it creates.

Infinity is subtle, yet bold, it is a Metallic paint that can enhance a room and create a stunning feature without appearing out of place. By behaving like the velvet material, it creates a colour difference that mimics being brushed in different directions.

Application Instructions

Infinity is ready to use, and can be applied on new and old plasters, concrete surfaces, gypsum plasters, plasterboards, MDF and timber after Infinity primer.

It can be applied using a Venetian Plastering Trowel. Infinity should not be diluted, but in case of extreme heat or suction, it can be diluted by water up to 5%.

Surface Preparation

Make sure the surface is completely dry, dust free and that all impurities have been removed. In case of mould, treat the surface with suitable specific product(s). Brush or remove any efflorescence and old peeling paint or wallpaper. If you are planning to apply Infinity on a dusty, chalky or high porous area, you should use Atomo (**to be applied before Infinity primer**). This will help to consolidate the surface. Once the surface has been prepared, you must apply Infinity primer diluted (150mL of water for 0.5L of primer, and 300mL of water for 1L of primer) prior to the paint application. Wait for 2 – 4 hours for the primer to get completely dry.

Before applying Infinity, stir the pot, and apply the first coat using a Venetian Plastering Trowel. Avoid using linear movements, the idea is to create a random pattern using varied motions. Give this coat adequate time to dry.

Begin the second coat using the trowel again, continuing to repeat the varied hand movements. At this stage, it is possible to be more deliberate with the pattern being created. The idea is to have random strokes that carry purpose and show off different shades according to the light reflecting off the surface.

INFINITY

Cleaning of the Tools

Tools should be cleaned immediately after use with water.

Technical Specifications

1 KG of Infinity covers approximately 5 sqm depending on the thickness of the application.

Recommendations

Do not apply Infinity if the substrate, air or product temperature is lower than +5C and higher than + 30C and kept out of direct sunlight.