

SIOLOC **SUEDE**

Product description

Sioloc Suede is a **semi-matt silky wall paint** that can be used for any indoor project. Once you apply it can create a soft, suede-like look with overlapping layers. It is extremely easy to apply, you can create several stunning effects with contemporary or traditional design quickly

Application Instructions

Sioloc Suede can be applied using a flexible plastic trowel or medium pile roller. Sioloc should not be diluted, but in case of extreme heat or suction it can be diluted by water up to 5%.

Surface Preparation

Make sure the surface is completely dry, dust free and all impurities have been removed. In case of mould, treat the surface with suitable specific products. Brush or remove any efflorescence and old peeling paint or wallpaper. If you are planning to apply Sioloc Suede on a dusty, chalky or high porous area, you should use Atomo (To be applied before Sioloc Suede primer). This will help to consolidate the surface. Once the surface has been prepared you must dilute the primer. Wait for 2 to 4 hours for the primer to get completely dry. Before applying Sioloc Suede, stir the pot and apply it with a flexible plastic trowel. The finish will be touch dry within an hour and completely dry after 1- 2 hours.

Cleaning of tools

Tools should be cleaned immediately after use with water.

Technical Specifications

1 Kg of Sioloc Suede covers approx 8-10 Sqm depends on thickness of application.

Recommendations:

Do not apply Sioloc Suede if the substrate, air or product temperature is lower than +5°C and higher than +35°C, nor under direct sun light.

Storage

Storage temperature 5- 30 °C Sioloc Suede paint should be used preferably within 2 years from date of purchase and should be stored in the original container, under the appropriate temperature conditions.

